



OAWH Architectural Aluminum Wall Fan Heater



With surface mounting box Recessed



Features

Color

- Standard: white, almond, metallic silver, bronze, metallic charcoal, aluminum, semi-gloss black, sand.
- Custom colors available upon request.

Finish

- Standard: epoxy/polyester powder paint.
- Optional: anodized aluminum.

Voltage

- 120V, 208V, 240/208V, 277V, 347V, 480V, 600V, 1 or 3-phase.

Construction

- Extruded aluminum front grille, 1/8 in. (3.2 mm) thick. **1**
- Bottom air outlet.
- High-limit temperature control with automatic reset.

Fan

- Closed, factory-lubricated motor.
- 160 cfm fan (single unit: 55 dBA); 2 X 160 cfm fan (double unit: 58 dBA), 3 X 160 cfm fan (triple unit: 61 dBA). **2**
- Fan delay purges heater of residual heat.

Heating element

- Durable tubular heating element with fins. **3**

Control

- Built-in tamperproof thermostat included. **4**
- 24V relay, with or without transformer available.

Note: Thermostat is not included in heater with factory installed relay. Any remote thermostat or relay must be connected to the heater control terminal block.

Installation

- Minimum clearance from the floor and adjacent walls: 10 in. (25.4 cm).
- Surface mounting box available.
- Semi recessed trim kit available.

Warranty

- 3-year warranty against defects.

Application

- Apartment building, commercial building, entrance way, stairwell, garage.

Watts	Volts (ph)	Product # ¹	Price	BTU/hr	Unit	Weight	
						lb	kg
1500	120 (1)	OAWH01502-TAV	926.00	5123	single	24.0	10.9
2000	208 (1)	OAWH02008-TAV	1103.00	6830	single	24.0	10.9
4000	208 (1)	OAWH04008-TAV	1103.00	13661	single	24.0	10.9
4000	208 (3)	OAWH04038-TAV	1348.00	13661	single	28.0	13.0
4800	208 (1)	OAWH04808-TAV	1157.00	16393	single	24.0	10.9
5000	208 (3)	OAWH05038-TAV	1537.00	17076	single	28.0	12.7
6000	208 (3)	OAWH06038-TAV	2392.00	20491	double	56.0	25.4
8000	208 (1)	OAWH08008-TAV	2460.00	27321	double	50.0	22.7
9000	208 (3)	OAWH09038-TAV	3064.00	30737	triple	90.0	40.9
12000	208 (1)	OAWH12008-TAV	3701.00	40982	triple	90.0	40.9
12000	208 (3)	OAWH12038-TAV	3701.00	40982	triple	90.0	40.9
1500/1125 ²	240/208 (1)	OAWH01500-TAV	926.00	5123/3842	single	24.0	10.9
2000/1500 ²	240/208 (1)	OAWH02000-TAV	926.00	6830/5123	single	24.0	10.9
3000/2250 ²	240/208 (1)	OAWH03000-TAV	949.00	10246/7684	single	24.0	10.9
3000/2250 ²	240/208 (3)	OAWH03030-TAV	1157.00	10246/7684	single	28.0	13.0
4000/3000 ²	240/208 (1)	OAWH04000-TAV	1011.00	13661/10246	single	24.0	10.9
4000/3000 ²	240/208 (3)	OAWH04030-TAV	1260.00	13661/10246	single	28.0	13.0
4800/3600 ²	240/208 (1)	OAWH04800-TAV	1064.00	16393/12295	single	24.0	10.9
5000/3750 ²	240/208 (3)	OAWH05030-TAV	1485.00	17076/12807	single	28.0	12.7
6000/4500 ²	240/208 (1)	OAWH06000-TAV	2177.00	20491/15368	double	50.0	22.7
8000/6000 ²	240/208 (1)	OAWH08000-TAV	2328.00	27321/20491	double	50.0	22.7
12000/9000 ²	240/208 (1)	OAWH12000-TAV	3586.00	40982/30737	triple	90.0	40.9
1500	347 (1)	OAWH01507-TAV	1313.00	5123	single	24.0	10.9
2000	347 (1)	OAWH02007-TAV	1313.00	6830	single	24.0	10.9
3000	347 (1)	OAWH03007-TAV	1355.00	10246	single	24.0	10.9
4000	347 (1)	OAWH04007-TAV	1391.00	13661	single	24.0	10.9
4800	347 (1)	OAWH04807-TAV	1471.00	16393	single	24.0	10.9
6000	347 (1)	OAWH06007-TAV	2825.00	20491	double	55.0	25.0
8000	347 (1)	OAWH08007-TAV	3243.00	27321	double	55.0	25.0
12000	347 (1)	OAWH12007-TAV	4650.00	40982	triple	90.0	40.9
1500	480 (1)	OAWH01504-TAV	1373.00	5123	single	28.0	12.7
2000	480 (1)	OAWH02004-TAV	1373.00	6830	single	28.0	12.7
3000	480 (1)	OAWH03004-TAV	1412.00	10246	single	28.0	12.7
3000	480 (3)	OAWH03034-TAV	1625.00	10246	single	32.0	15.0
4000	480 (1)	OAWH04004-TAV	1457.00	13661	single	28.0	12.7
4000	480 (3)	OAWH04034-TAV	1695.00	13661	single	32.0	15.0
4800	480 (1)	OAWH04804-TAV	1533.00	16393	single	28.0	12.7
5000	480 (3)	OAWH05034-TAV	1969.00	17076	single	32.0	15.0
6000	480 (1)	OAWH06004-TAV	2830.00	20491	double	55.0	25.0
8000	480 (1)	OAWH08004-TAV	3243.00	27321	double	55.0	25.0
12000	480 (1)	OAWH12004-TAV	4650.00	40982	triple	90.0	40.9
12000	480 (3)	OAWH12034-TAV	4650.00	40982	triple	90.0	40.9
1500	600 (1)	OAWH01506-TAV	1373.00	5123	single	28.0	12.7
2000	600 (1)	OAWH02006-TAV	1373.00	6830	single	28.0	12.7
3000	600 (1)	OAWH03006-TAV	1412.00	10246	single	28.0	12.7
3000	600 (3)	OAWH03036-TAV	1625.00	10246	single	32.0	15.0
4000	600 (1)	OAWH04006-TAV	1457.00	13661	single	28.0	12.7
4000	600 (3)	OAWH04036-TAV	1695.00	13661	single	32.0	15.0
4800	600 (1)	OAWH04806-TAV	1533.00	16393	single	28.0	12.7
5000	600 (3)	OAWH05036-TAV	1969.00	17076	single	32.0	15.0
6000	600 (1)	OAWH06006-TAV	2830.00	20491	double	55.0	25.0
6000	600 (3)	OAWH06036-TAV	2942.00	20491	double	60.0	27.2
8000	600 (1)	OAWH08006-TAV	3243.00	27321	double	55.0	25.0
9000	600 (3)	OAWH09036-TAV	3845.00	30737	triple	90.0	40.9
12000	600 (1)	OAWH12006-TAV	4650.00	40982	triple	90.0	40.9
12000	600 (3)	OAWH12036-TAV	4650.00	40982	triple	90.0	40.9

¹ Built-in tamperproof thermostat included.

² 208V = 75% of wattage at 240V.

Add "BL" for white, "AM" for almond, "AE" for metallic silver, "BZ" for bronze, "CM" for mettalic charcoal, "AL" for aluminum, "NL" for semi-gloss black, «SA» for sand. 277V available upon request.

OAWH

Options

Product # Kit	Product # Factory installed*	Price	Description
KIT-OAWH-BSA	-	132.00	Surface mounting box, single unit
KIT-OAWH-BSA1-1	-	132.00	Semi recessed 1 in. trim kit, single unit
KIT-OAWH-BSA1-2	-	132.00	Semi recessed 2 in. trim kit, single unit
KIT-OAWH-BSA2	-	264.00	Surface mounting box, double unit
KIT-OAWH-BSA2-1	-	264.00	Semi recessed 1 in. trim kit, double unit
KIT-OAWH-BSA2-2	-	264.00	Semi recessed 2 in. trim kit, double unit
KIT-OAWH-BSA3	-	396.00	Surface mounting box, triple unit
KIT-OAWH-BSA3-1	-	396.00	Semi recessed 1 in. trim kit, triple unit
KIT-OAWH-BSA3-2	-	396.00	Semi recessed 2 in. trim kit, triple unit
KIT-OAWH-DIS20 ³	DIS20 ³	187.00	Disconnect switch, double-pole, 20A at 277V and less
KIT-OAWH-DIS40 ³	DIS40 ³	217.00	Disconnect switch, triple-pole, 40A at 600V max.
KIT-OAWH-DIS80 ³	DIS80 ³	264.00	Disconnect switch, triple-pole, 80A at 600V max.
-	IV	187.00	Fan switch
-	R ⁴	197.00	24V control relay, without transformer
-	RT ⁴	208.00	24V control relay, with transformer

* For factory installed options, add the option number to the product number. See the **Product Code** section inside the front cover.

³ For the U.S. only: The nominal current of the unit must not exceed 80% of the capacity of the disconnect.

⁴ If the built-in thermostat is not required with the 24V control relay, remove the "-TAV" from the product number (E.g.: OAWH04006-RT).

