

# OCC OCC-WB

## Portable Construction Heater Unit Heater with Bracket



### Grounded 3-Pronged Outlet



NEMA 6-20R  
20A, 250VAC



NEMA 6-30R  
30A, 250VAC

### Features

#### Color

- Standard: almond.

#### Finish

- Standard: epoxy/polyester powder paint.

#### Voltage

- 240/208V, 1-phase.

#### Construction

- 6 ft. (2 m) molded electric cable for extra durability.
- Safely recessed thermostat knob reduces heater size to a minimum.
- High-limit temperature control with automatic reset (first level) and single operation thermal fuse (second level).

#### Fan

- 300 cfm fan.

#### Heating element

- Helical coil nickel-chromium alloy wire protected by ceramic insulators
- Heating element provides instant heat.

#### Temperature rise

- 28 °C (51 °F).

#### Control

- Built-in thermostat included.

#### Installation

- 4000W must be plugged into a grounded 3-pronged outlet, 20A, 250VAC.
- 4800W must be plugged into a grounded 3-pronged outlet, 30A, 250VAC.

Note: Always unplug heater when not in use.

### Features OCC

#### Construction

- Handle may be used as a reel for the electric cable.

#### Fan

- Open motor permanently lubricated.

Note: The open motor is not intended for use in a dusty environment.

#### Warranty

- 2-year warranty against defects.

#### Application

- Construction area, workshop, garage.

### Features OCC-WB

#### Construction

- Carrying handle also use as attach point for the bracket.

#### Fan

- Enclosed motor permanently lubricated.

#### Installation

- Wall or ceiling mounting using the supplied bracket which allow 360° rotation of the heater and prevent it from tipping over.

#### Warranty

- 3-year warranty against defects.

#### Application

- Workshop, shed, garage.

### Models

Product #	Volts	Watts	Grounded 3-Pronged Outlet	Weight	
				lb	kg
OCCU4000AM-MO-TB6 <sup>1</sup>	240/208	4000/3000	20A, 250VAC	16.0	7.3
OCCU4800AM-MO-TB6 <sup>1</sup>	240/208	4800/3600	30A, 250VAC	16.0	7.3
OCCU4000AMWB-MF-TB6 <sup>2</sup>	240/208	4000/3000	20A, 250VAC	16.0	7.3
OCCU4800AMWB-MF-TB6 <sup>2</sup>	240/208	4800/3600	30A, 250VAC	16.0	7.3

<sup>1</sup> Built-in thermostat included.

<sup>2</sup> Built-in thermostat and mounting bracket included. Standard color is almond.

