Universal Guards





On/Off Relays

Product #	Price	Volts 60 Hz	Resistive Charge (A)
Without transform	er		
RC840	55.00	120/208/240	22
KC840	55.00	347	18
R841D1036	105.00	600	10
With transformer			
RC840T-120	103.00	120	22
RC840T-240	74.00	208/240	22
RC840T-347	75.00	347	18
R841C1151	122.00	600	10

Note: Not recommended for fast-cycling modulated regulation (more than 6 cycles/hr). For fast-cycling heating equipment Solid State Relay.

Meant for external installation only. For installation inside heaters, refer to the options table

of the concerned product series.

Triac Relays

Product #	Price	Volts 60 Hz	Resistive Charge (A)	Input Signal	
Without transformer					
RT850	79.00	100 to 347	23	4-32VDC, 24VAC	
CCT-25-1-C1	117.00	208/240/347	25	3-32VDC, 24VAC	
CCT-30-1-C2	151.00	48-600	30	3-32VDC, 24VAC	
With transformer					
RT850T-240	93.00	208/240	23	19.2/24VAC	
RT850T-347	89.00	347	23	24VAC	
CCT-25-1-C2-T	117.00	208/240/277/347	25	14.4/16.6/19.2/24VAC	

Note: Meant for external installation only. For installation inside heaters, refer to the options table of the concerned product series.

Universal Guards

Product #	Price	Description	Inside Dimension (Length X Height X Depth)
F29-0143	46.00	Clear plastic thermostat guard	6 3/8 in. X 3 1/2 in. X 3 in.
F29-0198	46.00		8 1/4 in. X 5 3/8 in. X 3 1/2 in.
F29-0193	74.00	Metal thermostat guard	6 in. X 3 13/16 in. X 3 1/8 in.