


# OACP Commercial Ceiling Fan Heater



## Features

### Color

- Standard: white, almond.
- Optional (upcharge applicable): metallic silver, bronze, metallic charcoal, aluminum, semi-gloss black, sand.
- Custom colors available upon request.

### Finish

- Standard: epoxy/polyester powder paint.

### Voltage

- 120V, 208V, 240/208V, 277V, 347V, 480V, 600V, 1-phase.

### Construction

- 18-gauge steel front cover.
- High-limit temperature control with automatic reset.

### Fan

- Factory-lubricated motor (open and ventilated).
- 160 cfm fan (single unit: 55.5 dBA), 2 X 160 cfm fan (double unit: 58.5 dBA).
- Fan delay purges heater of residual heat.

### Heating element

- Durable tubular heating element with fins.

### Control

- 240/208V control circuit standard with contactor when needed (except 120V model).
- 24V relay, with or without transformer available.
- Built-in thermostat available.

*Note: If an electronic thermostat is used, it must be compatible with forced-air heaters.*

*Any remote thermostat or relay must be connected to the heater control terminal block.*

### Installation











- Maximum recommended installation height: 10 ft. (3 m).
- Minimum clearance from adjacent walls: 10 in. (25.4 cm).
- Surface mounting box available.
- Adaptor for T-bar ceiling available.

### Warranty

- 3-year warranty against defects.

### Application

- Apartment building, commercial building, drop ceiling, stairwell, garage.



Installation (All Models)

# OACP

## Models

Watts	Volts (1 ph)	Product #	Price	BTU/hr	Unit	Weight	
						lb	kg
1500	120	OACP1502	822.00	5123	single	24.0	10.9
2000	208	OACP2008	964.00	6820	single	24.0	10.9
4000	208	OACP4008	964.00	13661	single	24.0	10.9
4800	208	OACP4808	1009.00	16393	single	24.0	10.9
8000	208	OACP8008	2252.00	27321	double	50.0	22.7
1500/1125 <sup>1</sup>	240/208	OACP1500	880.00	5123/3842	single	24.0	10.9
2000/1500 <sup>1</sup>	240/208	OACP2000	880.00	6830/5123	single	24.0	10.9
3000/2250 <sup>1</sup>	240/208	OACP3000	902.00	10246/7684	single	24.0	10.9
4000/3000 <sup>1</sup>	240/208	OACP4000	964.00	13661/10246	single	24.0	10.9
4800/3600 <sup>1</sup>	240/208	OACP4800	1009.00	16393/12295	single	24.0	10.9
6000/4500 <sup>1</sup>	240/208	OACP6000	1982.00	20491/15368	double	50.0	22.7
8000/6000 <sup>1</sup>	240/208	OACP8000	2130.00	27321/20491	double	50.0	22.7
1500	347	OACP1507	1168.00	5123	single	28.0	12.7
2000	347	OACP2007	1168.00	6830	single	28.0	12.7
3000	347	OACP3007	1209.00	10246	single	28.0	12.7
4000	347	OACP4007	1248.00	13661	single	28.0	12.7
6000	347	OACP6007	2602.00	20491	double	50.0	22.7
8000	347	OACP8007	2986.00	27321	double	50.0	22.7
1500	480	OACP1504	1232.00	5123	single	28.0	12.7
2000	480	OACP2004	1232.00	6830	single	28.0	12.7
3000	480	OACP3004	1272.00	10246	single	28.0	12.7
4000	480	OACP4004	1317.00	13661	single	28.0	12.7
6000	480	OACP6004	2602.00	20491	double	50.0	22.7
8000	480	OACP8004	2986.00	27321	double	50.0	22.7
1500	600	OACP1506	1232.00	5123	single	28.0	12.7
2000	600	OACP2006	1232.00	6830	single	28.0	12.7
3000	600	OACP3006	1272.00	10246	single	28.0	12.7
4000	600	OACP4006	1317.00	13661	single	28.0	12.7
4800	600	OACP4806	1387.00	16393	single	28.0	12.7
6000	600	OACP6006	2602.00	20491	double	50.0	22.7
8000	600	OACP8006	2986.00	27321	double	50.0	22.7

## Options

Product # Kit	Product # Factory installed*	Price	Description
KIT-OAWH-BSA	-	132.00	Surface mounting box for an extruded aluminum front grille, single unit
KIT-OAWH-BSA2	-	264.00	Surface mounting box for an extruded aluminum front grille, double unit
KIT-OAC-BS1	-	95.00	Surface mounting box, single unit
KIT-OAC-BS2	-	190.00	Surface mounting box, double unit
KIT-OAC-DVA	-	332.00	Extruded aluminum front grille, single unit
KIT-OAC-DVA2	-	670.00	Extruded aluminum front grille, double unit
KIT-OACP-DIS20 <sup>2</sup>	DIS20 <sup>2</sup>	184.00	Disconnect switch, double-pole, 20A at 240V
KIT-OACP-DIS40 <sup>2</sup>	DIS40 <sup>2</sup>	212.00	Disconnect switch, triple-pole, 40A at 600V
KIT-OACP-R	R	193.00	24V control relay, without transformer
-	RT	204.00	24V control relay, with transformer
KIT-OACP-T	T	153.00	Thermostat
KIT-OACP-T-BAR	-	95.00	Adaptor for T-bar ceiling installation, 23 3/4 in. X 23 3/4 in. (602 mm X 602 mm), single unit
KIT-OACP-T-BAR2	-	190.00	Adaptor for T-bar ceiling installations, 23 3/4 in. X 47 11/16 in. (602 mm X 1211 mm), double unit

\* For factory installed options, add the option number to the product number. See the **Product Code** section inside the front cover.

<sup>1</sup> 208V = 75% of wattage at 240V.

<sup>2</sup> For the U.S. only: The nominal current of the unit must not exceed 80% of the capacity of the disconnect. Add "BL" for white, "AM" for almond. Upcharge available for optional colors shown in the color chart section. 277V available upon request.