

# OCL Standard Convector



## Features

### Color

- Standard: white.
- Optional (upcharge applicable): almond, metallic silver, bronze, aluminum, semi-gloss black, metallic charcoal, sand.
- Custom colors available upon request.

### Finish

- Standard: epoxy/polyester powder paint.

### Voltage

- 120V, 208V, 240/208V, 277V, 347V, 480V, 600V, 60 Hz, 1-phase.

### Construction

- 20-gauge steel.
- Top warm air outlet for rapid, even heat distribution throughout the room and optimum efficiency.
- Openings preventing insertion of foreign objects.
- High-limit temperature control with automatic reset.

### Heating element

- 2 stainless steel tubular heating elements with aluminum fins.
- Floating heating element on high-temperature nylon bushings reducing expansion noises.

### Watt density

- 700W/ft. (2320W/m).

### Control

- Built-in non programmable electronic thermostat for the 120V to 240V models (-TH models).
- Wall thermostat (not included).

### Installation

- 4 in. (102 mm) minimum clearance to floor and from an adjacent wall.
- Quick surface-mounted installation, with the included wall mounting bracket.
- Single-screw built-in wire holder for quick access to the junction box.
- Optional kit of 10 BX wire-holding plates, for installing an AC90 type electrical cable.

### Warranty

- 5-year warranty against defects.

*Ouellet highly recommends the use of an electronic wall thermostat for greater comfort.*

### Application

- Kitchen, living room, family room, office, bedroom, basement, entrance hall.

Models

Volts	Watts	Product #		Price		Length		Weight	
		Without thermostat		Built-in thermostat		in.	mm	lb	kg
120	500	OCL0502BL	173.00	OCL0502BL-TH	238.00	18	457	13	6
120	1000	OCL1002BL	222.00	OCL1002BL-TH	287.00	23 9/16	598	16.7	7.6
120	1500	OCL1502BL	250.00	OCL1502BL-TH	315.00	29 1/16	739	20	9.12
208	500	OCL0508BL	173.00	OCL0508BL-TH	238.00	18	457	13	6
208	1000	OCL1008BL	222.00	OCL1008BL-TH	287.00	23 9/16	598	16.7	7.6
208	1500	OCL1508BL	250.00	OCL1508BL-TH	315.00	29 1/16	739	20	9.12
208	2000	OCL2008BL	288.00	OCL2008BL-TH	353.00	34 5/8	880	24	10.9
240/208	500/375	OCL0500BL	188.00	OCL0500BL-TH	253.00	18	457	13	6
240/208	1000/750	OCL1000BL	208.00	OCL1000BL-TH	273.00	23 9/16	598	16.7	7.6
240/208	1500/1125	OCL1500BL	238.00	OCL1500BL-TH	303.00	29 1/16	739	20	9.12
240/208	2000/1500	OCL2000BL	273.00	OCL2000BL-TH	338.00	34 5/8	880	24	10.9
347	500	OCL0507BL	221.00	-	-	18	457	13	6
347	1000	OCL1007BL	271.00	-	-	23 9/16	598	16.7	7.6
347	1500	OCL1507BL	299.00	-	-	29 1/16	739	20	9.12
347	2000	OCL2007BL	337.00	-	-	34 5/8	880	24	10.9
600	1000	OCL1006BL	271.00	-	-	23 9/16	598	16.7	7.6
600	1500	OCL1506BL	299.00	-	-	29 1/16	739	20	9.12
600	2000	OCL2006BL	337.00	-	-	34 5/8	880	24	10.9

Options

Product # Kit	Product # Factory installed*	Price	Description
KIT-SERF-BX	-	144.00	Kit of 10 BX wire-holding plates, for installing an AC90 type electrical cable
KIT-OCL-TRIAC-347	TRIAC	77.00	Single-pole electronic relay, coil 24V, without transformer: 15A at 347V max.
KIT-OCL-TRIAC-347T	TRIAC T	103.00	Single-pole electronic relay, coil 24V, with transformer: 15A at 208V, 240V, 277V, 347V
KIT-OCL-TRIAC-600	TRIAC	139.00	Single-pole electronic relay, coil 24V, without transformer: 6A at 600V max.

\* For factory installed options, add the option number to the product number. See the **Product Code** section inside the front cover.  
Standard color is white.  
Other voltages available upon request.

