

OCB Heavy-Duty Aluminum Draft Barrier



With bottom fresh air inlet and pedestals



Features

Color

- Standard: white, almond.
- Optional (upcharge applicable): metallic silver, bronze, metallic charcoal, aluminum, semi-gloss black, sand.
- Custom colors available upon request.

Finish

- Standard: epoxy/polyester powder paint.
- Optional: anodized aluminum.

Voltage

- 120V, 208V, 240/208V, 277V, 347V, 600V, 50/60 Hz, 1-phase.

Construction

- 14-gauge (0.0787 in. [2 mm]) aluminum front cover.
- 18-gauge satin coat steel cabinet.
- Full length built-in wireway.
- Separate low voltage wireway (-WW) available.
- Pencil-proof openings less than 1/4 in. (6.4 mm).
- Front fresh air inlet; top warm air outlet.
 - Bottom fresh air inlet available (-BAI).
- Clean back available (-BD).
- Linear high-limit temperature control with automatic reset.
- End caps included.

Heating element

- Stainless steel tubular heating element with aluminum fins.
- Floating heating elements on high-temperature nylon bushings reducing expansion noises.

Watt density

- Standard watt density.
- Low watt density.

Control

- Built-in thermostat available with a control knob or tamperproof (installed on the right end only).
- Mechanical, electronic or pneumatic relays available (installed on the right end only).

Ouellet highly recommends to use an electronic wall thermostat for greater comfort.

Installation

- Heater must be installed at least 3 in. (76 mm) from finished floor (for -BAI option).
- Mounting holes spaced on 1 in. (25.4 mm) intervals for ease of installation.
- Wall or floor mounted installation.
- Variety of accessories available for wall-to-wall installation.
- Pedestal kit available.

Warranty

- 1-year warranty against defects.

Application

- Commercial building, office building, hospital, daycare center, private residence.

Standard Watt Density Models

Watts	Watts 240/208V	Product #				Length		Weight	
		120V	208V	240/208V	277V	in.	mm	lb	kg
500	500/375	OCB0502	OCB0508	OCB0500	OCB0577	28	711	8.0	3.6
750	750/563	OCB0752	OCB0758	OCB0750	OCB0777	38	965	10.8	4.9
1000	1000/750	OCB1002	OCB1008	OCB1000	OCB1077	48 3/16	1224	13.7	6.2
1250	1250/938	OCB1252	OCB1258	OCB1250	OCB1277	57 11/16	1465	16.4	7.5
1500	1500/1125	OCB1502	OCB1508	OCB1500	OCB1577	66 7/16	1687	18.8	8.6
1750	1750/1313	-	OCB1758	OCB1750	OCB1777	75 13/16	1925	21.5	9.8
2000	2000/1500	-	OCB2008	OCB2000	OCB2077	84 9/16	2148	24.0	10.9
2250	2250/1688	-	OCB2258	OCB2250	OCB2277	93 1/2	2375	26.5	12.1
2500	2500/1875	-	OCB2508	OCB2500	OCB2577	102 5/8	2606	29.1	13.2

Low Watt Density Models

Product # ¹	Length	Weight	Average Density W/ft.	Watts	Watts 240/208V ¹	120V	208V	240/208V	277V
OCB020X-711	28" (711mm)	8.0 lb (3.6 kg)	100	200	200/150	✓	✓	✓	✓
OCB030X-711			150	300	300/225	✓	✓	✓	✓
OCB040X-711			200	400	400/300	✓	✓	✓	✓
OCB030X-965	38" (965 mm)	10.8 lb (4.9 kg)	100	300	300/225	✓	✓	✓	✓
OCB045X-965			150	450	450/338	✓	✓	✓	✓
OCB060X-965			200	600	600/450	✓	✓	✓	✓
OCB040X-1224	48 3/16" (1224 mm)	13.7 lb (6.2 kg)	100	400	400/300	✓	✓	✓	✓
OCB060X-1224			150	600	600/450	✓	✓	✓	✓
OCB080X-1224			200	800	800/600	✓	✓	✓	✓
OCB050X-1465	57 11/16" (1465 mm)	16.4 lb (7.5 kg)	100	500	500/375	✓	✓	✓	✓
OCB075X-1465			150	750	750/563	✓	✓	✓	✓
OCB100X-1465			200	1000	1000/750	✓	✓	✓	✓
OCB060X-1687	66 7/16" (1687 mm)	18.8 lb (8.6 kg)	100	600	600/450	✓	✓	✓	✓
OCB090X-1687			150	900	900/675	✓	✓	✓	✓
OCB120X-1687			200	1200	1200/900	✓	✓	✓	✓
OCB070X-1925	75 13/16" (1925 mm)	21.5 lb (9.8 kg)	100	700	700/525	✓	✓	✓	✓
OCB105X-1925			150	1050	1050/788	✓	✓	✓	✓
OCB140X-1925			200	1400	1400/1050	✓	✓	✓	✓
OCB080X-2148	84 9/16" (2148 mm)	24.0 lb (10.9 kg)	100	800	800/600	✓	✓	✓	✓
OCB120X-2148			150	1200	1200/900	✓	✓	✓	✓
OCB160X-2148			200	1600	1600/1200	✓	✓	✓	✓
OCB090X-2375	93 1/2" (2375 mm)	26.5 lb (12.1 kg)	100	900	900/675	✓	✓	✓	✓
OCB135X-2375			150	1350	1350/1013	-	✓	✓	✓
OCB180X-2375			200	1800	1800/1350	-	✓	✓	✓
OCB100X-2606	102 5/8" (2606 mm)	29.1 lb (13.2 kg)	100	1000	1000/750	✓	✓	✓	✓
OCB150X-2606			150	1500	1500/1125	-	✓	✓	✓
OCB200X-2606			200	2000	2000/1500	-	✓	✓	✓

¹ X = 2 (120V), 8 (208V), 0 (240/208V), 77 (277V).

✓ = Available.

Add "BL" for white, "AM" for almond. Upcharge available for optional colors shown in the color chart section.

Other colors, accessories and finishes are available upon request. Please contact your customer service representative.

Other voltages available upon request.

Options

Product # Kit	Product # Factory installed*	Description
-	BAI	Bottom fresh air inlet
-	BD ¹	Clean back
KIT-OCB-CE	-	Outside corner, 6 in. (152 mm)
KIT-OCB-CI	-	Inside corner, 6 in. (152 mm)
KIT-OCB-JT	-	Splice plate, 1 3/16 in. (30 mm)
KIT-OCB-JT-PE	-	Contour splice plate for BD option and/or heater with pedestals, 1 3/16 po (30 mm)
KIT-OCB-PE	-	Round pedestal kit (2), 3 in. (76 mm)
KIT-OCB-PEC	-	Square-shaped pedestal kit (2), 3 in. (76 mm)
OCB-SV-XX	-	Empty cabinet with length of XX mm (minimum: 154 mm, maximum: 2606 mm)
KIT-OCB-DIS20 ³	DIS20 ³	Disconnect switch, 20A at 277V max.
-	PM	Pneumatic relay, 20A at 600V max.
KIT-OCB-R-347	R	Single-pole relay, coil 24V, without transformer, 22A at 120V, 208V, 240V - 19A at 277V - 18A at 347V
KIT-OCB-R-600	R	Single-pole relay, coil 24V, without transformer, 10A at 600V
KIT-OCB-RT-120	RT	Single-pole relay, coil 24V, with transformer 120V/24V, 22A at 120V
KIT-OCB-RT-208	RT	Single-pole relay, coil 24V, with transformer 208V/24V, 22A at 208V
KIT-OCB-RT-240	RT	Single-pole relay, coil 24V, with transformer 240V/24V, 22A at 240V
KIT-OCB-RT-277	RT	Single-pole relay, coil 24V, with transformer 277V/24V, 19A at 277V
KIT-OCB-RT-347	RT	Single-pole relay, coil 24V, with transformer 347V/24V, 18A at 347V
KIT-OCB-RT-600 ²	RT ²	Single-pole relay, coil 24V, with transformer 600V/24V, 10A at 600V (2-wire only)
KIT-OCB-T	T	Single-pole thermostat: 30A at 120V, 208V, 240V - 15A at 277V, 347V, 600V
KIT-OCB-T ² ⁴	T ² ⁴	Double-pole thermostat: 30A at 120V, 208V, 240V - 15A at 347V, 600V
KIT-OCB-T-AV	TAV	Single-pole tamperproof thermostat: 30A at 120V, 208V, 240V - 15A at 277V, 347V, 600V
KIT-OCB-T ² -AV ⁴	T ² AV ⁴	Double-pole tamperproof thermostat: 30A at 120V, 208V, 240V - 15A at 347V, 600V
KIT-OCB-TRIAC-347	TRIAC	Single-pole electronic relay, coil 24V, without transformer, 15A at 347V max.
KIT-OCB-TRIAC-347T	TRIACT	Single-pole electronic relay, coil 24V, with transformer, 15A at 208V, 240V, 347V
KIT-OCB-TRIAC-600	TRIAC	Single-pole electronic relay, coil 24V, without transformer, 6A at 600V max.
-	WW	24V wireway

* For factory installed options, add the option number to the product number. See the **Product Code** section inside the front cover.

¹ For anodized aluminum heaters, the clean back option will be fixed with visible rivets.

² These 2-wire relays with transformer can't supply of 3-wire low voltage thermostats.

³ For the U.S. only: The nominal current of the unit must not exceed 80% of the capacity of the disconnect.

⁴ "Off" position.

