

ONC Standard Convector



Features

Color

- Standard: white.
- Optional (upcharge applicable): almond, metallic silver, bronze, aluminum, semi-gloss black, metallic charcoal, sand.
- Custom colors available upon request.

Finish

- Standard: epoxy/polyester powder paint.

Voltage

- 120V, 208V, 240/208V, 277V, 347V, 480V, 600V, 60 Hz, 1-phase.

Construction

- 20-gauge steel.
- Warm air outlet that directs the air to the center of the room.
- Bar grilles prevent insertion of foreign objects.
- High-limit temperature control with automatic reset.

Heating element

- 2 stainless steel tubular heating elements with aluminum fins.
- Floating heating element on high-temperature nylon bushings reducing expansion noises.

Watt density

- 700W/ft. (2320W/m).

Control

- Built-in non programmable electronic thermostat for the 120V to 240V models (-TH models).
- Wall thermostat (not included).

Installation

- 4 in. (102 mm) minimum clearance to floor and from an adjacent wall.
- Quick surface-mounted installation, with the included wall mounting bracket.

Warranty

- 5-year warranty against defects.

Ouellet highly recommends the use of an electronic wall thermostat for greater comfort.

Application

- Kitchen, living room, family room, bedroom, basement.

ONC

Models

| Volts | Watts | Product # | | Length | | Weight | |
|---------|-----------|--------------------|---------------------|---------|-----|--------|------|
| | | Without thermostat | Built-in thermostat | in. | mm | lb | kg |
| 120 | 500 | ONCU0502BL | ONCU0502BL-TH | 18 | 457 | 13 | 6 |
| 120 | 1000 | ONCU1002BL | ONCU1002BL-TH | 23 9/16 | 598 | 16.7 | 7.6 |
| 120 | 1500 | ONCU1502BL | ONCU1502BL-TH | 29 1/16 | 739 | 20 | 9.12 |
| 208 | 500 | ONCU0508BL | ONCU0508BL-TH | 18 | 457 | 13 | 6 |
| 208 | 1000 | ONCU1008BL | ONCU1008BL-TH | 23 9/16 | 598 | 16.7 | 7.6 |
| 208 | 1500 | ONCU1508BL | ONCU1508BL-TH | 29 1/16 | 739 | 20 | 9.12 |
| 208 | 2000 | ONCU2008BL | ONCU2008BL-TH | 34 5/8 | 880 | 24 | 10.9 |
| 240/208 | 500/375 | ONCU0500BL | ONCU0500BL-TH | 18 | 457 | 13 | 6 |
| 240/208 | 1000/750 | ONCU1000BL | ONCU1000BL-TH | 23 9/16 | 598 | 16.7 | 7.6 |
| 240/208 | 1500/1125 | ONCU1500BL | ONCU1500BL-TH | 29 1/16 | 739 | 20 | 9.12 |
| 240/208 | 2000/1500 | ONCU2000BL | ONCU2000BL-TH | 34 5/8 | 880 | 24 | 10.9 |
| 277 | 500 | ONCU0577BL | - | 18 | 457 | 13 | 6 |
| 277 | 1000 | ONCU1077BL | - | 23 9/16 | 598 | 16.7 | 7.6 |
| 277 | 1500 | ONCU1577BL | - | 29 1/16 | 739 | 20 | 9.12 |
| 277 | 2000 | ONCU2077BL | - | 34 5/8 | 880 | 24 | 10.9 |
| 480 | 1000 | ONCU1004BL | - | 23 9/16 | 598 | 16.7 | 7.6 |
| 480 | 1500 | ONCU1504BL | - | 29 1/16 | 739 | 20 | 9.12 |
| 480 | 2000 | ONCU2004BL | - | 34 5/8 | 880 | 24 | 10.9 |

Options

| Product # Kit | Product # Factory installed* | Description |
|---------------------|---------------------------------|---|
| KIT-ONCU-TRIAC-347 | TRIAC | Single-pole electronic relay, coil 24V, without transformer, 15A at 347V max. |
| KIT-ONCU-TRIAC-347T | TRIAC T | Single-pole electronic relay, coil 24V, with transformer, 15A at 208V, 240V, 277V, 347V |
| KIT-ONCU-TRIAC-600 | TRIAC | Single-pole electronic relay, coil 24V, without transformer, 6A at 600V max. |

* For factory installed options, add the option number to the product number. See the **Product Code** section inside the front cover.
 Standard color is white.
 Upcharge applicable for optional colors shown in the color chart section.
 Other voltages available upon request.

