

OSM-AF AirForce™ Multi Nozzle High Velocity Hand Dryer
OSM-AD AirDuo Hand and Hair Dryer
OSM-AT AirTempest Hand Dryer



AirForce™



AirDuo



AirTempest



AirTempest only



Features

AirForce™
Multi Nozzle High Velocity Hand Dryer

Color

- White, chrome.

Finish

- White: epoxy paint incorporated with SteriTouch® antimicrobial additive.
- Chrome: plating.

Voltage

- 120V, 240V, 1-phase.

Construction

- Die cast aluminum housing.

Sound level

- 85.1 dBA with hands.

Heating element

- No heating element.

Control

- Activated by an automatic active infrared sensor controlled by a circuit board with 1-second run-on time and 30-second vandal shut-off.

Installation

- Surface-mounted.

Warranty

- 5-year warranty against defects.

AirDuo
Hand and Hair Dryer

Color

- Standard: white.

Finish

- Standard: epoxy paint.

Voltage

- 120V, 240/208V, 1-phase.

Construction

- Die cast aluminum housing.

Sound level

- 74 dBA with hands.

Heating element

- Helical coil nickel-chromium alloy wire protected by mica insulator.

Control

- Pushbutton with micro-switch activated timer. Time cycle setting can be adjusted in the field from 15-second to 3-minute.

Installation

- Surface-mounted.

Warranty

- 5-year warranty against defects.

AirTempest
Hand Dryer

Color

- Standard: white, stainless steel.

Finish

- Standard: epoxy paint.
- Optional: stainless steel.

Voltage

- Automatically adjusts itself to all power conditions, from 120V to 240V.

Construction

- Epoxy painted steel, stainless steel.

Fan

- Thermally-protected universal type, 1/8 HP, 4800 RPM.

Sound level

- 67dBA without hands.

Heating element

- Nichrome wire construction, 1200 watts, and auto-reset thermal-protector so power is disconnected if air is not flowing.

Control

- Automatic touch-free infrared sensor.

Installation

- Surface-mounted with security screws to prevent vandalism (tool supplied).

Warranty

- 5-year warranty against defects.

Models

Product #	Color	Watts	Volts	Weight	
				lb	kg
AirForce™					
J-974	White	1100	120	7.0	3.2
J4-974	White		240	7.0	3.2
J-970	Chrome		120	7.0	3.2
J4-970	Chrome		240	7.0	3.2
AirDuo					
OAD1802BL	White	1800	120	18.0	8.2
OAD1800BL	White	1800/1350	240/208	18.0	8.2
AirTempest					
OAM90BL	White	400-1400 (120V)	120 to 240	9.4	4.2
OAM90SS	Stainless steel	350-1250 (240V)			

OSM-VD OSM-SD

VERDEdri™ Slim Profile High Velocity Hand Dryer

SMARTdri™ Plus Versatile Hand Dryer



VERDEdri™



SMARTdri™



VERDEdri™

IP24



SMARTdri™ Plus



IP24

Features

VERDEdri™

Slim Profile High Velocity Hand Dryer

Color

- Standard: white.
- Optional: black, brushed stainless steel.

Voltage

- Universal voltage 110 to 240V, 1-phase.

Construction

- Die cast aluminum housing.
- Optional Hepa filter.

Sound level

- 87 dBA with hands high speed.
- 70 dBA with hands low speed.

Heating element

- No heating element.

Control

- Adjustable two speed controls to customize drying time, sound level and energy savings.

Installation

- ADA compliant surface-mounted.

Warranty

- 5-year warranty against defects.

SMARTdri™ Plus

Versatile Hand Dryer

Color

- Standard: white.
- Optional: black, brushed stainless steel.

Voltage

- 120V, 240/208V, 1-phase.

Construction

- Die cast aluminum housing.

Sound level

- 73 to 85 dBA with hands.

Heating element

- Helical coil nickel-chromium alloy wire protected by mica insulator.

Control

- 3 speeds motor settings and on/off heating option.

Installation

- Surface-mounted.

Warranty

- 5-year warranty against defects.

Models

Product #	Color	Watts	Volts	Weight	
				lb	kg
VERDEdri™					
Q-974A	White	950	110 to 240	9.8	4.4
Q-162A	Black	950	110 to 240	9.8	4.4
Q-973A	Stainless steel	950	110 to 240	11.3	5.1
SMARTdri™ Plus					
K-974P	White	400-1200	120	11.6	5.2
K4-974P	White	425-1250	240/208	11.6	5.2
K-162P	Black	400-1200	120	11.6	5.2
K4-162P	Black	425-1250	240/208	11.6	5.2
K-973P	Stainless steel	400-1200	120	14.2	6.4
K4-973P	Stainless steel	425-1250	240/208	14.2	6.4

Option¹

Product # Kit	Description
93-10292	Hepa filter

¹ For VERDEdri™ only.