


Options

| Product # Kit | Price | Description |
|---|---------|--|
| OSR-NA Series | | |
| ECA-JB1 | 355.00 | Junction box for single connection c/w label and fastener |
| ECA-JB2 | 506.00 | Junction box for double connection c/w label and fastener |
| EL-CLIC-P | 260.00 | Quick connector with supply lead, for 1 to 3 cables |
| EL-CLIC-S | 247.00 | Quick connector for direct connection or cold lead connection of 1 to 3 cables |
| EL-ECN-EX ¹ | 25.00 | End termination for ELSR-NA and ELSR-WA |
| EL-SPN-16 | 37.00 | Heat shrink splice-kit suitable for ELSR-NA and cold lead connections |
| ELAK-3-7 | 626.00 | Junction box with mounting stand for non-hazardous (ordinary) and hazardous locations |
| ELVB-SRAN | 46.00 | Power connection without cable gland |
| ELVB-SRAN-12-PA | 64.00 | Power connection with plastique/PA12 cable gland/fitting, 1/2" NPT, non-hazardous location |
| ELVB-SRAN-34-PA | 67.00 | Power connection with plastique/PA12 cable gland/fitting, 3/4" NPT, non-hazardous location |
| ELVB-SRAN-34-ST | 80.00 | Power connection with steel/zinc cable gland/fitting, 3/4" NPT, non-hazardous location |
| ELVB-SREX-34-HT ¹ | 216.00 | Power connection with nickel plated cable gland, 3/4" NPT, hazardous location |
| ELVB-SREX-M20-HT ¹ | 192.00 | Power connection with nickel plated cable gland, M20, hazardous location |
| KIT-OSR-DRD-120V | 1521.00 | Roof drain de-icing kit with 50' of 120V 7w/ft. OSR-NA cable (ELSR-NA-7-1-BO) |
| KIT-OSR-DRD-240V | 1521.00 | Roof drain de-icing kit with 50' of 240V 8w/ft. OSR-NA cable (ELSR-NA-8-2-BO) |
| KIT-OSR-ELSR-NA | 92.00 | End and power termination kit with warning sticker NA Series |
| OSR-MA Series (AO and BO outer jacket) | | |
| EL-ECM ¹ | 24.00 | End termination for ELSR-MA |
| ELVB-SRAM | 46.00 | Power connection without cable gland |
| ELVB-SRAM-34-ST | 80.00 | Power connection with steel/zinc cable gland/fitting, 3/4" NPT, non-hazardous location |
| KIT-OSR-ELSR-MA | 92.00 | End and power termination kit with warning sticker MA Series |
| OSR-MA Series (BF outer jacket) | | |
| EL-ECMF ² | 34.00 | End termination for ELSR-MA-BF |
| ELVB-SRAM-34-ST | 80.00 | Power connection with steel/zinc cable gland/fitting, 3/4" NPT, non-hazardous location |
| KIT-OSR-ECA-MABF-PH-FIT | 56.00 | Brass gland cable fitting 3/4" NPT non-hazardous location for MA-BF cable |
| KIT-OSR-ELSR-MA-BF | 104.00 | End and power termination kit with warning sticker BF Series |
| KIT-OSR-MABF-PH-1-CTSOD ³ | 107.00 | Quick connect plumbing kit for 1" OD polyethylene CTS pipes for MA-BF cable |
| KIT-OSR-MABF-PH-114-CTSOD ³ | 125.00 | Quick connect plumbing kit for 1 1/4" OD polyethylene CTS pipes for MA-BF cable |
| KIT-OSR-MABF-PH-112-CTSOD ³ | 163.00 | Quick connect plumbing kit for 1 1/2" OD polyethylene CTS pipes for MA-BF cable |
| KIT-OSR-MABF-PH-34-ID ³ | 96.00 | Quick connect plumbing kit for 3/4" ID polyethylene pipes for MA-BF cable |
| KIT-OSR-MABF-PH-1-ID ³ | 125.00 | Quick connect plumbing kit for 1" ID polyethylene pipes for MA-BF cable |
| KIT-OSR-MABF-PH-114-ID ³ | 141.00 | Quick connect plumbing kit for 1 1/4" ID polyethylene pipes for MA-BF cable |
| KIT-OSR-MABF-PH-112-ID ³ | 227.00 | Quick connect plumbing kit for 1 1/2" ID polyethylene pipes for MA-BF cable |
| OSR-WA Series | | |
| EL-CLIC-P | 260.00 | Quick connector with supply lead, for 1 to 3 cables |
| EL-CLIC-S | 247.00 | Quick connector for direct connection or cold lead connection of 1 to 3 cables |
| EL-ECN-EX ¹ | 25.00 | End termination for ELSR-NA and ELSR-WA |
| ELVB-SRAW | 55.00 | Power connection without cable gland |
| ELVB-SRAW-34-ST | 88.00 | Power connection with steel/zinc cable gland, 3/4" NPT, non-hazardous location |
| KIT-OSR-ELSR-WA | 95.00 | End and power termination kit with warning sticker WA Series |
| OSR-HA Series | | |
| ECA-JB1 | 355.00 | Junction box for single connection c/w label and fastener |
| ECA-JB2 | 506.00 | Junction box for double connection c/w label and fastener |
| EL-ECH-EX ¹ | 25.00 | End termination for ELSR-HA |
| ELAK-3-7 | 626.00 | Junction box with mounting stand for non-hazardous (ordinary) and hazardous locations |
| ELVB-SRAH | 46.00 | Power connection without cable gland |
| ELVB-SRAH-34-ST | 80.00 | Power connection with steel/zinc cable gland/fitting, 3/4" NPT, non-hazardous location |
| ELVB-SREX-34-HT ¹ | 216.00 | Power connection with nickel plated cable gland, 3/4" NPT, hazardous location |
| ELVB-SREX-M20-HT ¹ | 192.00 | Power connection with nickel plated cable gland, M20, hazardous location |
| KIT-OSR-ELSR-HA | 92.00 | End and power termination kit with warning sticker HA Series |



EL-EC(x)



ELVB-SRA(x)



ELVB-SRA(x)-34-ST




KIT-OSR-ELSR-xx



KIT-OSR-MABF-PH-xx-CTSOD



KIT-OSR-MABF-PH-xx-ID



ECA-JB1

¹ Minimum installation temperature -45 °C (-49 °F).

² Minimum installation temperature -13 °C (-25 °F).

³ Identifying the type of pipe is key to ensuring a simple and effective connection, Ouellet Canada is not responsible for incorrect pipe selection. No returns will be accepted.

Options

| Product # Kit | Price | Description |
|------------------------------|-------|---|
| All OSR Series | | |
| Multiple applications | | |
| KIT-OSR-EL-WS03 | 2.00 | Warning label/sign bilingual (English / French) |
| Roof and gutter | | |
| ELB-20 | 14.00 | Stainless steel downspout 90° mounting plate with nylon ties |
| ELB-21 | 18.00 | Stainless steel gutter mounting plate with nylon ties |
| ELB-RCLIP | 44.00 | Roof clips for cable, qty 25 |
| Pipe tracing | | |
| ELB-02B | 61.00 | Self-adhesive glass fiber tape, max. temp. = 90 °C (194 °F), 165 ft. (50 m) |
| ELB-06 | 57.00 | Self-adhesive aluminum tape max. temp. 140 °C (284 °F) 165 ft. (50 m) |
| ELB-06C | 46.00 | Self-adhesive aluminum tape, max. temp. = 80 °C (176 °F), 165 ft. (50 m) |

Controls

| Product # | Price | Description |
|--|---------|---|
| Controller options for roof and gutter for de-icing | | |
| DS-2C ¹ | 889.00 | Aerial mounted controller with sensor to detect humidity and temperature, 30A: 100V to 277V, 20A: 28VDC |
| DS-8C ¹ | 953.00 | Aerial mounted controller with sensor to detect temperature and a sensor to detect humidity with 10 ft. (3 m) cable, 30A, 100V to 277V |
| DS-9C ¹ | 953.00 | Aerial mounted controller with sensor to detect temperature and a sensor to detect humidity with 10 ft. (3 m) cable, 2 x 30A, 100V to 277V |
| EX-50 | 257.00 | 50 ft. (15 m) extension kit, with connection fittings for humidity sensor |
| CDP-2 | 291.00 | Interior controller and display for DS products |
| ETO2 ¹ | 825.00 | Dual-zone electronic controller, 1-zone: 3 x 16A, 2-zone: 2 x 16A, 120V to 240V |
| ETF-744-99 | 206.00 | 24V outdoor sensor for measuring temperature |
| ETOR-55 | 401.00 | Gutter sensor to detect humidity with 33 ft. (10 m) cable |
| Controller options for pipe tracing for use in non-hazardous (ordinary) locations | | |
| ECA-E55-R25HT ¹ | 1620.00 | SPDT, NEMA 4X thermostat in molded aluminum housing, 22A at 120/250/480V, with 10 ft. (3 m) stainless steel bulb and capillary |
| TPR-L1N-3X-Q10 ¹ | 495.00 | SPDT, NEMA 4X thermostat in polycarbonate housing, 22A at 120/250/480V, with 3 ft. (1 m) tinned copper bulb and capillary |
| TPR-L1N-10X-Q10 ¹ | 645.00 | SPDT, NEMA 4X thermostat in polycarbonate housing, 22A at 120/250/480V, with 10 ft. (3 m) tinned copper bulb and capillary |
| TRF115-005 ¹ | 174.00 | SPDT, NEMA 4X thermostat, range -17 °C to 49 °C (0 °F to 120 °F), 25A at 120/208/240/277V, with 5 ft. (1.5 m) stainless steel bulb and capillary |
| TRF115-007 ¹ | 179.00 | SPDT, NEMA 4X thermostat, range -35 °C to 38 °C (-30 °F to 100 °F), 25A at 120/208/240/277V, with 8 ft. (2.4 m) copper bulb and capillary |
| ELTC-14-RTD ¹ | 898.00 | Digital temperature control 20A at 90-260V, including 3-wire RTD (Pt-100) sensing element is 5 x 50 mm with 5 m of fluoropolymer lead wires, range 0 °C to 250 °C (32 °F to 482 °F). Suitable for used with GFPE panels |
| GPT-130 | 1608.00 | NEMA 4X IP66 electronic single point line sensing heat trace controller 100-277V, 30A c/w built-in 30 mA GFEP and 20 ft. (6 m) lead, 100k ohms at 25 °C(77 °F) thermistor. Range -40 °C to 110 °C (-40 °F to 230 °F) |
| S1-A | 2964.00 | NEMA 4X IP67 electronic single point line sensing heat trace controller 100-277V, 30A c/w built-in 30 mA GFEP and 20' (6 m) lead, 10k ohms thermistor, Wi-Fi, Ethernet, Modbus and BACnet ³ capabilities |
| S1-B | 2054.00 | NEMA 4X IP67 electronic single point line sensing heat trace controller 100-277V, 30A c/w built-in 30 mA GFEP and 20' (6 m) lead, 10k ohms thermistor, Wi-Fi, Ethernet |
| GATEWAY-PCKG | 4524.00 | 24VDC BACnet gateway assembly with power supply NEMA 4X enclosure with 24VDC transformer for S1 Series |
| GATEWAY | 3276.00 | 24VDC BACnet gateway stand alone for S1 Series |
| Controller options for pipe tracing for use in non-hazardous (ordinary) and hazardous locations | | |
| E121-13273 ¹ | 1664.00 | Explosion -proof NEMA 4X 7, 9 and IP66 epoxy painted die cast aluminum line sensing thermostat temperature control 120-480V, 22A, SPDT c/w 10 ft. (3 m) stainless steel capillary, |
| TM-1SIH1-E5-RTD-A1 | 2395.00 | TraceMate™ I GFCI electronic thermostat for single circuit at 120V, 30A |
| TM-1DIH2-E5-RTD-A1 | 2851.00 | TraceMate™ I GFCI electronic thermostat for single circuit at 240/208V, 30A |
| TM-2SIH1-E5-RTD | 4015.00 | TraceMate™ II GFCI electronic thermostat for dual circuit at 120V, 2 x 30A |
| TM-2DIH2-E5-RTD | 4809.00 | TraceMate™ II GFCI electronic thermostat for dual circuit at 240/208V, 2 x 30A |
| MS-2101 ² | 4672.00 | MasterTrace Single circuit electronic GFCI controller with double pole, 85V to 300V, 30A, with user interface |
| MS-2102 ² | 5617.00 | MasterTrace Double circuit electronic GFCI controller with single pole, 120V or 277V, 2 x 30A, with user interface |
| RTD-7 | 406.00 | RTD probe for MasterTrace controller |
| Control panel options | | |
| SR-4CIR-240 | 5876.00 | 4 circuits 240V 30A circuit GFEP control panel with contactors and 240-120V control transformer (HxWxD: 20x16x8 in.) |
| SR-6CIR-240 | 6396.00 | 6 circuits 240V 30A circuit GFEP control panel with contactors and 240-120V control transformer (HxWxD: 20x16x8 in.) |
| SR-8CIR-240 | 6994.00 | 8 circuits 240V 30A circuit GFEP control panel with contactors and 240-120V control transformer (HxWxD: 24x20x8 in.) |
| SR-12CIR-240 | 8138.00 | 12 circuits 240V 30A circuit GFEP control panel with contactors and 240-120V control transformer (HxWxD: 24x24x8 in.) |

¹ Requires a ground fault circuit interrupter (GFCI) in the electrical panel.

² Requires a RTD probe for MasterTrace controller (RTD-7).

³ BACnet IP or MS/TP available via preconfigured SMC gateway, sold separately.

