


OAWH

Architectural Aluminum Wall Fan Heater



With surface
mounting box

Recessed



Features

Color

- Standard: white, almond, metallic silver, bronze, metallic charcoal, aluminum, semi-gloss black, sand.
- Custom colors available upon request.

Finish

- Standard: epoxy/polyester powder paint.
- Optional: anodized aluminum.

Voltage

- 120V, 208V, 240/208V, 277V, 347V, 480V, 600V, 1 or 3-phase.

Construction

- Extruded aluminum front grille, 1/8 in. (3.2 mm) thick. 1
- Bottom air outlet.
- High-limit temperature control with automatic reset.

Fan

- Closed, factory-lubricated motor.
- 160 cfm fan (single unit: 55 dBA); 2 X 160 cfm fan (double unit: 58 dBA), 3 X 160 cfm fan (triple unit: 61 dBA). 2
- Fan delay purges heater of residual heat.

Heating element

- Durable tubular heating element with fins. 3

Control

- Built-in tamperproof thermostat included. 4
- 24V relay, with or without transformer available.

Note: Thermostat is not included in heater with factory installed relay. Any remote thermostat or relay must be connected to the heater control terminal block.

Installation

- Minimum clearance from the floor and adjacent walls: 10 in. (25.4 cm).
- Surface mounting box available.
- Semi recessed trim kit available.

Warranty

- 5-year warranty against defects.

Application

- Apartment building, commercial building, entrance way, stairwell, garage.

Product # ¹	Volts (ph)	Watts	BTU/hr	Weight		Unit
				lb	kg	
OAWH01502-TAV	120 (1)	1500	5123	24.0	10.9	single
OAWH02008-TAV	208 (1)	2000	6830	24.0	10.9	single
OAWH04008-TAV	208 (1)	4000	13661	24.0	10.9	single
OAWH04038-TAV	208 (3)	4000	13661	28.0	13.0	single
OAWH04808-TAV	208 (1)	4800	16393	24.0	10.9	single
OAWH05038-TAV	208 (3)	5000	17076	28.0	12.7	single
OAWH06038-TAV	208 (3)	6000	20491	56.0	25.4	double
OAWH08008-TAV	208 (1)	8000	27321	50.0	22.7	double
OAWH09038-TAV	208 (3)	9000	30737	90.0	40.9	triple
OAWH12008-TAV	208 (1)	12000	40982	90.0	40.9	triple
OAWH12038-TAV	208 (3)	12000	40982	90.0	40.9	triple
OAWH01500-TAV ²	240/208 (1)	1500/1125	5123/3842	24.0	10.9	single
OAWH02000-TAV ²	240/208 (1)	2000/1500	6830/5123	24.0	10.9	single
OAWH03000-TAV ²	240/208 (1)	3000/2250	10246/7684	24.0	10.9	single
OAWH03030-TAV ²	240/208 (3)	3000/2250	10246/7684	28.0	13.0	single
OAWH04000-TAV ²	240/208 (1)	4000/3000	13661/10246	24.0	10.9	single
OAWH04030-TAV ²	240/208 (3)	4000/3000	13661/10246	28.0	13.0	single
OAWH04800-TAV ²	240/208 (1)	4800/3600	16393/12295	24.0	10.9	single
OAWH05030-TAV ²	240/208 (3)	5000/3750	17076/12807	28.0	12.7	single
OAWH06000-TAV ²	240/208 (1)	6000/4500	20491/15368	50.0	22.7	double
OAWH08000-TAV ²	240/208 (1)	8000/6000	27321/20491	50.0	22.7	double
OAWH12000-TAV ²	240/208 (1)	12000/9000	40982/30737	90.0	40.9	triple
OAWH01577-TAV	277 (1)	1500	5123	24.0	10.9	single
OAWH02077-TAV	277 (1)	2000	6830	24.0	10.9	single
OAWH03077-TAV	277 (1)	3000	10246	24.0	10.9	single
OAWH04077-TAV	277 (1)	4000	13661	24.0	10.9	single
OAWH04877-TAV	277 (1)	4800	16393	24.0	10.9	single
OAWH06077-TAV	277 (1)	6000	20491	55.0	25.0	double
OAWH08077-TAV	277 (1)	8000	27321	55.0	25.0	double
OAWH12077-TAV	277 (1)	12000	40982	90.0	40.9	triple
OAWH01504-TAV	480 (1)	1500	5123	28.0	12.7	single
OAWH02004-TAV	480 (1)	2000	6830	28.0	12.7	single
OAWH03004-TAV	480 (1)	3000	10246	28.0	12.7	single
OAWH03034-TAV	480 (3)	3000	10246	32.0	15.0	single
OAWH04004-TAV	480 (1)	4000	13661	28.0	12.7	single
OAWH04034-TAV	480 (3)	4000	13661	32.0	15.0	single
OAWH04804-TAV	480 (1)	4800	16393	28.0	12.7	single
OAWH05034-TAV	480 (3)	5000	17076	32.0	15.0	single
OAWH06004-TAV	480 (1)	6000	20491	55.0	25.0	double
OAWH08004-TAV	480 (1)	8000	27321	55.0	25.0	double
OAWH12004-TAV	480 (1)	12000	40982	90.0	40.9	triple
OAWH12034-TAV	480 (3)	12000	40982	90.0	40.9	triple

¹ Built-in tamperproof thermostat included.

² 208V = 75% of wattage at 240V.

Add "BL" for white, "AM" for almond, "AE" for metallic silver, "BZ" for bronze, "CM" for mettalic charcoal, "AL" for aluminum, "NL" for semi-gloss black, «SA» for sand.

Options

Product # Kit	Product # Factory installed*	Description
KIT-OAWH-BSA	-	Surface mounting box, single unit
KIT-OAWH-BSA1-1	-	Semi recessed 1 in. trim kit, single unit
KIT-OAWH-BSA1-2	-	Semi recessed 2 in. trim kit, single unit
KIT-OAWH-BSA2	-	Surface mounting box, double unit
KIT-OAWH-BSA2-1	-	Semi recessed 1 in. trim kit, double unit
KIT-OAWH-BSA2-2	-	Semi recessed 2 in. trim kit, double unit
KIT-OAWH-BSA3	-	Surface mounting box, triple unit
KIT-OAWH-BSA3-1	-	Semi recessed 1 in. trim kit, triple unit
KIT-OAWH-BSA3-2	-	Semi recessed 2 in. trim kit, triple unit
KIT-OAWH-DIS20 ³	DIS20 ³	Disconnect switch, double-pole, 20A at 277V and less
KIT-OAWH-DIS40 ³	DIS40 ³	Disconnect switch, triple-pole, 40A at 600V max.
KIT-OAWH-DIS80 ³	DIS80 ³	Disconnect switch, triple-pole, 80A at 600V max.
-	IV	Fan switch
-	R ⁴	24V control relay, without transformer
-	RT ⁴	24V control relay, with transformer

* For factory installed options, add the option number to the product number. See the **Product Code** section inside the front cover.

³ For the U.S. only: The nominal current of the unit must not exceed 80% of the capacity of the disconnect.

⁴ If the built-in thermostat is not required with the 24V control relay, remove the "-TAV" from the product number (E.g.: OAWH04004-RT).

