

# OVN Electronic Bathroom Fan Heater



Training available online [www.ouellet.com](http://www.ouellet.com)

## Features

### Color

- Standard: white, almond.
- Optional (upcharge applicable): metallic silver, bronze, metallic charcoal, aluminum, semi-gloss black, sand.
- Custom colors available upon request.

### Finish

- Standard: epoxy/polyester powder paint.

### Voltage

- 240/208V, 1-phase.

### Construction

- Cast aluminum front cover.
- Steel bar grilles prevents the insertion of foreign objects; smooth-finish paint is washable and anti-yellowing.
- High-limit temperature control with automatic reset.

### Fan

- Whisper-quiet squirrel-cage fan.
- Factory-lubricated, two-speed motor.

### Heating element

- Nickel-chromium alloy stitched wire protected by mica insulators.
- Heating element provides instant heat.

### Control

- Built-in electronic digital thermostat/timer with backlit display that can be used as a night light.
- Electronic thermostat with 2 triacs automatically switches from 750W to 1500W when needed.
- Electronic boost heating mode: 1-30 minutes.
- Standby mode, ideal for cottages.
- Keypad lock function that eliminates unwanted temperature adjustments and the use of the thermostat modes.

### Installation

- 4 in. (102 mm) minimum clearance to floor.
- May be recessed or surface-mounted without adaptor in 2 in. X 3 in. stud partitions with gypsum.
- Single-screw built-in wire holder and mounting holes for fast and easy installation.
- Template included.

### Warranty

- 5-year warranty against defects.

### Application

- Bathroom, kitchen, living room, entrance way.

## Model

Watts		Volts	Product #	Price	Weight	
min.	max.				lb	kg
750/563	1500/1125	240/208	OVN1500-TH	527.00	16.3	7.4

## Option

Product # Kit	Product # Factory installed*	Price	Description
KIT-OVN-DIS <sup>1</sup>	DIS <sup>1</sup>	99.00	Disconnect switch, 20A at 250V

\* For factory installed options, add the option number to the product number. See the **Product Code** section inside the front cover.

<sup>1</sup> For the U.S. only: The nominal current of the unit must not exceed 80% of the capacity of the disconnect.

Add "BL" for white, "AM" for almond.

Upcharge available for optional colors shown in the color chart section.

