



OCL Series Standard Convecteur



Modern, simple and discreet design

To match any decor

Optimum heat efficiency

Top air outlet for rapid, even heat distribution throughout the room

Slimmer profile

Saves space with a more compact convecteur

Natural convection

Offering a whisper-quiet machine





Built-in electronic thermostat in option

Simple and easy to use

Models

Volts	Watts	Product #		Length		Weight	
		Without thermostat	Built-in thermostat	in.	mm	lb	kg
120	500	OCL0502BL	OCL0502BL-TH	18	457	13	6
120	1000	OCL1002BL	OCL1002BL-TH	23 9/16	598	16.7	7.6
120	1500	OCL1502BL	OCL1502BL-TH	29 1/16	739	20	9.12
208	500	OCL0508BL	OCL0508BL-TH	18	457	13	6
208	1000	OCL1008BL	OCL1008BL-TH	23 9/16	598	16.7	7.6
208	1500	OCL1508BL	OCL1508BL-TH	29 1/16	739	20	9.12
208	2000	OCL2008BL	OCL2008BL-TH	34 5/8	880	24	10.9
240/208	500/375	OCL0500BL	OCL0500BL-TH	18	457	13	6
240/208	1000/750	OCL1000BL	OCL1000BL-TH	23 9/16	598	16.7	7.6
240/208	1500/1125	OCL1500BL	OCL1500BL-TH	29 1/16	739	20	9.12
240/208	2000/1500	OCL2000BL	OCL2000BL-TH	34 5/8	880	24	10.9
347	500	OCL0507BL	-	18	457	13	6
347	1000	OCL1007BL	-	23 9/16	598	16.7	7.6
347	1500	OCL1507BL	-	29 1/16	739	20	9.12
347	2000	OCL2007BL	-	34 5/8	880	24	10.9
600	1000	OCL1006BL	-	23 9/16	598	16.7	7.6
600	1500	OCL1506BL	-	29 1/16	739	20	9.12
600	2000	OCL2006BL	-	34 5/8	880	24	10.9