OSM-AD AirDuo Hand and Hair Dryer OSM-AT

OSM-AF AirForce™ Multi Nozzle High Velocity Hand Dryer

AirTempest Hand Dryer















Features

AirForce[™]

Multi Nozzle High Velocity Hand Dryer

• White, chrome.

Finish

- White: epoxy paint incorporated with SteriTouch® antimicrobial additive.
- · Chrome: plating.

Voltage

• 120V, 240V, 1-phase.

Construction

• Die cast aluminum housing.

Sound level

• 85.1 dBA with hands.

Heating element

• No heating element.

Control

• Activated by an automatic active infrared sensor controlled by a circuit board with 1-second run-on time and 30-second vandal shut-off.

Installation

· Surface-mounted.

Warranty

• 5-year warranty against defects.

AirDuo

Hand and Hair Dryer

· Standard: white.

Finish

• Standard: epoxy paint.

• 120V, 240/208V, 1-phase.

Construction

• Die cast aluminum housing.

Sound level

• 74 dBA with hands.

Heating element

· Helical coil nickel-chromium alloy wire.

Control

 Pushbutton with micro-switch activated timer. Time cycle setting can be adjusted in the field from 15-second to 3-minute.

Installation

· Surface-mounted.

Warranty

• 5-year warranty against defects.

AirTempest **Hand Dryer**

• Standard: white, stainless steel.

- Standard: epoxy paint.
- · Optional: stainless steel.

Voltage

 Automatically adjusts itself to all power conditions, from 120V to 240V.

Construction

• Epoxy painted steel, stainless steel.

• Thermally-protected universal type, 1/8 HP, 4800 RPM.

Sound level

• 67dBa without hands.

Heating element

· Nichrome wire construction, 1200 watts, and auto-reset thermal-protector so power is disconnected if air is not flowing.

· Automatic touch-free infrared sensor.

Installation

 Surface-mounted with security screws to prevent vandalism (tool supplied).

Warranty

• 5-year warranty against defects.

Models

| Product # | Price | Color | | V. b | Weight | |
|------------|---------|-----------------|-----------------|------------|--------|-----|
| | | | Watts | Volts | lb | kg |
| AirForce™ | | | | | | |
| J-974 | 1167.00 | White | | 120 | 7.0 | 3.2 |
| J4-974 | 1167.00 | White | 1100 | 240 | 7.0 | 3.2 |
| J-970 | 1343.00 | Chrome | 1100 | 120 | 7.0 | 3.2 |
| J4-970 | 1343.00 | Chrome | | 240 | 7.0 | 3.2 |
| AirDuo | | | | | | |
| OAD1802BL | 944.00 | White | 1800 | 120 | 18.0 | 8.2 |
| OAD1800BL | 944.00 | White | 1800/1350 | 240/208 | 18.0 | 8.2 |
| AirTempest | | | | | | |
| OAM90BL | 687.00 | White | 400-1400 (120V) | 120 to 240 | 9.4 | 4.2 |
| OAM90SS | 893.00 | Stainless steel | 350-1250 (240V) | | 9.4 | 4.2 |

OSM-VD VERDEdri™ Slim Profile High Velocity Hand Dryer OSM–SD SMARTdri™Plus Versatile Hand Dryer







VERDEdri™





SMARTdri™ Plus









Features

VERDEdri™

Slim Profile High Velocity Hand Dryer

Color

- · Standard: white.
- Optional: black, brushed stainless steel.

• Universal voltage 110 to 277V, 1-phase.

Construction

- HEPA flter eliminates 99.97% of particles 0.3µm or larger.
- Antimicrobial technology protects the treated surfaces on the dryer by inhibiting the growth of bacteria, mold and fungus that can cause stains, odors or deterioration
- IP24 rating protection against harmful water ingress.

Sound level

• 69 dBA without hands in airstream

Heating element

• Nichochrome wire construction, 475 watts, with auto-reset thermal protector so power is disconnected if air is not flowing.

Control

- 3 speed selector switch.
- · Automatic touch-free infrared activation with 45 second vandal-resistant lock out feature.
- 12 second drying time (adjustable).

Installation

- ADA compliant surface-mounted.
- Cover attached with tamper-resistant screws; security wrench included.

Warranty

• 10-year warranty against defects.

SMARTdri[™] Plus Versatile Hand Dryer

Color

- Standard: white.
- Optional: black, brushed stainless steel.

• 120V, 240/208V, 1-phase.

Construction

• Die cast aluminum housing.

Sound level

• 73 to 85 dBA with hands.

Heating element

• Helical coil nickel-chromium alloy wire.

Control

• 3 speeds motor settings and on/off heating option.

Installation

· Surface-mounted.

Warranty

• 5-year warranty against defects.

Models

| Product # | Price | Color | Watts | Volts | Weight | |
|--------------|---------|-----------------|-------------|------------|--------|-----|
| | | | | | lb | kg |
| VERDEdri™ | | | | | | |
| Q-974A2 | 1154.00 | White | 950 to 1150 | 110 to 277 | 8.3 | 3.7 |
| Q-162A2 | 1154.00 | Black | 950 to 1150 | 110 to 277 | 8.3 | 3.7 |
| Q-973A2 | 1404.00 | Stainless steel | 950 to 1150 | 110 to 277 | 9.9 | 4.4 |
| SMARTdri™ PI | us | | | | | |
| K-974P | 1316.00 | White | 400-1200 | 120 | 11.6 | 5.2 |
| K4-974P | 1316.00 | White | 425-1250 | 240/208 | 11.6 | 5.2 |
| K-162P | 1316.00 | Black | 400-1200 | 120 | 11.6 | 5.2 |
| K4-162P | 1316.00 | Black | 425-1250 | 240/208 | 11.6 | 5.2 |
| K-973P | 1468.00 | Stainless steel | 400-1200 | 120 | 14.2 | 6.4 |
| K4-973P | 1468.00 | Stainless steel | 425-1250 | 240/208 | 14.2 | 6.4 |