

# OFB Compact Wall Fan Heater



## Features

### Color

- Standard: white.

### Finish

- Standard: epoxy/polyester powder paint.

### Voltage

- 120V, 240/208V, 1-phase.

### Construction

- 20-gauge steel cabinet.
- Warm air outlet that directs the air downwards, towards the center of the room.
- Bar grille prevents insertion of foreign objects; smooth-finish paint is washable and anti-yellowing.
- Manual de-energize high-limit thermal protection.

### Fan

- Whisper-quiet squirrel-cage fan.
- Factory-lubricated motor.

### Heating element

- Nickel-chromium alloy stitched wire protected by mica insulators.
- Heating element provides instant heat.

### Control

- Line voltage control circuit for thermostat, timer or switch (not included, must be compatible with the selected voltage and wattage of the heater).

*Note: If an electronic thermostat is used, it must be compatible with forced-air heaters.*

### Installation

- Recommended installation height: max. 10 ft. (3 m), min. 6 ft. (1.8 m).
- Wattage must be selected at the time of wiring (750W or 1500W).
- Quick surface-mounted installation, with the included mounting bracket.
- Flexible cable with electrical wall box cover plate included.
- Requires installation of a wall electrical box not supplied.

### Warranty

- 2-year warranty against defects.
- 5-year warranty on the heating element.

### Application

- Bathroom, entrance way, stairwell.

## Models

Watts <sup>1</sup>	Volts	Product #	Weight	
			lb	kg
750 1500	120	OFB1502BL	8.1	3.7
750/563 1500/1125	240/208	OFB1500BL	8.1	3.7

<sup>1</sup> Wattage can be selected on site (750W or 1500W). Standard color is white.

