


OVR Register Wall Fan Heater



With Surface Mounting Box and Thermostat

Recessed with Thermostat



Features

Color

- Standard: white, almond.
- Optional (upcharge applicable): metallic silver, bronze, metallic charcoal, aluminum, semi-gloss black, sand.
- Custom colors available upon request.

Finish

- Standard: epoxy/polyester powder paint.

Voltage

- 120V, 208V, 240/208V, 1-phase.

Construction

- 20-gauge steel.
- High-limit temperature control with automatic reset.

Fan

- Quiet fan operating.
- 500W to 1000W; 40 cfm fan and 1250W to 2000W; 80 cfm fan.
- Factory-lubricated motor.

Heating element

- Durable tubular heating element with fins.
- Factory sealed element upon request.

Control

- Built-in thermostat available with a control knob or tamperproof.

Note: If an electronic thermostat is used, it must be compatible with forced-air heaters.

Installation

- The air outlet should be installed at least 10 in. (25.4 cm) above floor.
- Quick installation with recess box mounting holes.
- Large wiring compartment.
- May be recessed in 2 in. x 3 in. stud partitions.
- Surface mounting box available.
- Tight fit with V-shaped recess box.

Warranty

- 5-year warranty against defects.

Application

- Entrance way, kitchen, bathroom, family room, basement.

OVR

Models

Watts	Volts	Product #	Price	Weight	
				lb	kg
500	120	OVRU0502	348.00	9.0	4.1
750	120	OVRU0752	348.00	9.0	4.1
1000	120	OVRU1002	368.00	9.0	4.1
1250	120	OVRU1252	402.00	9.0	4.1
1500	120	OVRU1502	402.00	9.0	4.1
500/375	240/208	OVRU0500	339.00	9.0	4.1
750/563	240/208	OVRU0750	339.00	9.0	4.1
1000/750	240/208	OVRU1000	363.00	9.0	4.1
1250/938	240/208	OVRU1250	363.00	9.0	4.1
1500/1125	240/208	OVRU1500	398.00	9.0	4.1
2000/1500	240/208	OVRU2000	440.00	9.0	4.1
2000	208	OVRU2008	440.00	9.0	4.1

Options

Product # Kit	Product # Factory installed*	Price	Description
KIT-OVR-BS	-	73.00	Surface mounting box
KIT-OVR-DIS ³	DIS ³	179.00	Disconnect switch, 20A at 277V max.
-	ES ¹	33.00	With sealed element factory installed
KIT-OVR-TB6	TB6	75.00	Single-pole bi-metal thermostat
KIT-OVR-TB26 ²	TB26 ²	96.00	Double-pole bi-metal thermostat
KIT-OVR-TB6-AV	TB6AV	88.00	Single-pole bi-metal thermostat, tamperproof
KIT-OVR-TB26-AV ²	TB26AV ²	96.00	Double-pole bi-metal thermostat, tamperproof

* For factory installed options, add the option number to the product number. See the Product Code section inside the front cover.

¹ The option "sealed element" increases the reliability of these in humid environments. It does not completely eliminate the leakage currents of metal sheathed heating elements.

² "Off" position.

³ For the U.S. only: The nominal current of the unit must not exceed 80% of the capacity of the disconnect.

Add "BL" for white, "AM" for almond.

Upcharge available for optional colors shown in the color chart section.

