

# **DECOR** Architectural Ceramic Glass Patio Infrared Heater





Bluetooth control using the Aura Connect™ application.

**Features** 

#### Color

• Standard: black.

#### Finish

• Standard: powder paint.

#### Voltage

• 240/208V, 60 Hz, 1-phase.

#### Construction

- Weatherproof IP65 certified for outdoor use.
- 2 mm thickness aluminum extrusion casing.
- High quality aluminum optical reflector.
- Power cord of 6 ft. (1.8 m) hard-wired.
- 304 stainless steel ceramic glass trim.

#### Heating element

- Woven carbon filament infrared lamp inside a 15 mm Quartz tube.
- Element service life ± 8000h.

#### Wavelength

• Mid-wave (2 µm).

#### Control

- On/Off integrated regulator and a remote control with 6 heat settings.
- The heater can be wired to bypass the remote control if required (Junction box not included).

### Certification

• Comply with the standard UL2021:2015 Ed.4 and C22.2 No.46: 2013 Ed.9.

#### Installation

• Horizontal installation only.

۵ 1P65

**((T))**us

- Pivoting wall mounting brackets included.
- · Mounting brackets for ceiling suspension available as an option, must order separately (CFCEIL).
- Installation minimum clearances:
- -8 ft. (2.4 m) from floor.
- -8 in. (20.3 cm) from ceiling, 20 in. (50.8 cm) between the end of the unit to the wall and 20 in. (50.8 cm) between the longer side of the unit to the wall.
- Hard-wired into an electrical junction box (not included).

#### Warranty

• 1-year warranty against defects. • 90-day warranty on the element (for industrial applications only).

#### Application

• Temporary back-up heating, workshop, garage, solarium, pool and spa, balcony, patio, bar, restaurant, hotel, church.

## Model

| Watts     | Volts   | Product #1     | Price   |      | Dim  |     | nensions<br>H D |     | D   | Weight |     |
|-----------|---------|----------------|---------|------|------|-----|-----------------|-----|-----|--------|-----|
|           |         |                |         | in.  | mm   | in. | mm              | in. | mm  | lb     | kg  |
| 3000/2250 | 240/208 | ADGLASS-30240B | 1098.00 | 42.6 | 1082 | б   | 152.4           | 5   | 127 | 17     | 7.7 |

Standard color is black.

Wall mounting brackets included.

| C | ption                         |       |  |        | <b></b>         | 679 mm<br>26 11/16″ | <br>6 | 1/2″  |              |
|---|-------------------------------|-------|--|--------|-----------------|---------------------|-------|---|--------------|
|   | Product #<br><mark>Kit</mark> | Price | Description                              | r es l | ***<br>* *<br>* |                     | , L   | - <del>R</del> -P                               | $\sim$       |
|   | CFCEIL                        | 44.00 | Mounting brackets for ceiling suspension |        |                 |                     | <br>4 | $\langle \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \$ | $\checkmark$ |
|   |                               |       |  |        |                 |                     |       | ~   | 1            |

165 mm

**Front View**