



OPPM Mini Patio Door Baseboard Heater



Features

Color

- Standard: white, almond.
- Optional (upcharge applicable): metallic silver, bronze, metallic charcoal, aluminum, semi-gloss black, sand.
- Custom colors available upon request.

Finish

- Standard: epoxy/polyester powder paint.

Voltage

- 120V, 208V, 240/208V, 277V, 347V, 480V, 600V, 1-phase.

Construction

- So sturdy, it can be used as a step (18-gauge steel). **1**
- Linear high-limit temperature control with automatic reset. **2**

Heating element

- Stainless steel tubular heating element with aluminum fins. **3**
- Floating heating element on high-temperature nylon bushings reducing expansion noises.

Watt density

- Average standard watt density of 152W/ft.

Control

- Built-in thermostat available with a control knob or tamperproof (installed on the left end only).
- Mechanical or electronic relays available (installed on the right end only).

Ouellet highly recommends using an electronic wall thermostat for greater comfort.

Installation

- Not for residential use in the United States.
- 2 rows of mounting holes, every 2 in. (51 mm), for ease of installation.
- Variety of accessories available for wall-to-wall installation.
- Pedestal kit available.

Warranty

- 3-year warranty against defects.
- 10-year warranty on the heating element.

Application

- Patio door, bay window, commercial building, office building, condo, restaurant.

OPPM

Average Standard Watt Density Models 152W/ft.

| Watts | Product # | | | | Watts | Product # | Price | Length | | Weight | |
|-------|-----------|----------|----------|----------|-----------|-----------|--------|----------|----------|--------|------|
| | 120V | 208V | 347V | 600V | | | | 240/208V | 240/208V | in. | mm |
| 300 | OPPM0302 | OPPM0308 | - | - | 300/225 | OPPM0300 | 357.00 | 23 5/8 | 600 | 5.3 | 2.4 |
| 450 | OPPM0452 | OPPM0458 | OPPM0457 | - | 450/338 | OPPM0450 | 383.00 | 35 7/16 | 900 | 9.5 | 4.3 |
| 600 | OPPM0602 | OPPM0608 | OPPM0607 | - | 600/450 | OPPM0600 | 415.00 | 47 1/4 | 1200 | 12.2 | 5.5 |
| 750 | OPPM0752 | OPPM0758 | OPPM0757 | OPPM0756 | 750/563 | OPPM0750 | 443.00 | 59 1/16 | 1500 | 15.0 | 6.8 |
| 900 | OPPM0902 | OPPM0908 | OPPM0907 | OPPM0906 | 900/675 | OPPM0900 | 522.00 | 70 7/8 | 1800 | 17.8 | 8.1 |
| 1050 | OPPM1052 | OPPM1058 | OPPM1057 | OPPM1056 | 1050/788 | OPPM1050 | 553.00 | 82 11/16 | 2100 | 20.6 | 9.3 |
| 1200 | OPPM1202 | OPPM1208 | OPPM1207 | OPPM1206 | 1200/900 | OPPM1200 | 585.00 | 94 1/2 | 2400 | 23.4 | 10.6 |
| 1350 | OPPM1352 | OPPM1358 | OPPM1357 | OPPM1356 | 1350/1013 | OPPM1350 | 617.00 | 106 5/16 | 2700 | 26.2 | 11.9 |

Options

| Product # Kit | Product # Factory installed* | Price | Description |
|----------------------------------|------------------------------|--------------|---|
| - | BD | +10% | Clean back |
| KIT-OPPM-CE | - | 216.00 | Outside corner, 3 in. (76 mm) |
| KIT-OPPM-CI | - | 216.00 | Inside corner, 3 in. (76 mm) |
| KIT-OPPM-JT | - | 99.00 | Splice plate, 2 in. (51 mm) |
| KIT-OPPM-JT-PE | - | 152.00 | Contour splice plate for BD option and/or heater with pedestals, 2 in. (51 mm) |
| KIT-OPPM-PE | - | 207.00 | Round pedestal kit (2), 3 in. (76 mm) |
| KIT-OPPM-PEC | - | 207.00 | Square-shaped pedestal kit (2), 2 in. (51 mm) |
| KIT-OPPM-R-347 ¹ | R ¹ | 269.00 | Single-pole relay, coil 24V, without transformer, 22A at 208V, 240V - 19A at 277V - 18A at 347V |
| KIT-OPPM-R-600 ¹ | R ¹ | 269.00 | Single-pole relay, coil 24V, without transformer, 10A at 600V |
| KIT-OPPM-RT-208 ¹ | RT ¹ | 282.00 | Single-pole relay, coil 24V, with transformer 208V/24V, 22A at 208V |
| KIT-OPPM-RT-240 ¹ | RT ¹ | 282.00 | Single-pole relay, coil 24V, with transformer 240V/24V, 22A at 240V |
| KIT-OPPM-RT-277 ¹ | RT ¹ | 282.00 | Single-pole relay, coil 24V, with transformer 277V/24V, 19A at 277V |
| KIT-OPPM-RT-347 ¹ | RT ¹ | 282.00 | Single-pole relay, coil 24V, with transformer 347V/24V, 18A at 347V |
| OPPM-SV-XX | - | Upon Request | Empty cabinet length of XX mm (minimum : 154 mm, maximum : 2700 mm) |
| KIT-OPPM-TB6 ² | TB6 ² | 219.00 | Single-pole bi-metal thermostat: 25A at 120V, 208V, 240V, 277V - 10A at 347V, 480V, 600V |
| KIT-OPPM-TB26 ^{2,3} | TB26 ^{2,3} | 228.00 | Double-pole bi-metal thermostat: 25A at 120V, 208V, 240V, 277V - 10A at 347V, 480V, 600V |
| KIT-OPPM-TB6-AV ² | TB6AV ² | 219.00 | Single-pole bi-metal tamperproof thermostat: 25A at 120V, 208V, 240V, 277V - 10A at 347V, 480V, 600V |
| KIT-OPPM-TB26-AV ^{2,3} | TB26AV ^{2,3} | 228.00 | Double-pole bi-metal tamperproof thermostat: 25A at 120V, 208V, 240V, 277V - 10A at 347V, 480V, 600V |
| KIT-OPPM-TRIAC-347 ¹ | TRIAC ¹ | 110.00 | Single-pole electronic relay, coil 24V, without transformer, 10A max. (except for 1350W: 11.5A max.) at 347V max. |
| KIT-OPPM-TRIAC-347T ¹ | TRIACT ¹ | 157.00 | Single-pole electronic relay, coil 24V, with transformer, 10A max. (except for 1350W: 11.5A max.) at 208V, 240V, 347V |
| KIT-OPPM-TRIAC-600 ¹ | TRIAC ¹ | 208.00 | Single-pole electronic relay, coil 24V, without transformer, 6A at 600V max. |

* For factory installed options, add the option number to the product number. See the **Product Code** section inside the front cover.

¹ Options installed at right end only.

² Options installed at left end only.

³ "Off" position.

Add "BL" for white, "AM" for almond. Upcharge available for optional colors shown in the color chart section.

Other voltages available upon request.

