

OVO Residential Wall Fan Heater



Features

Color

- Standard: white.

Finish

- Standard: epoxy/polyester powder paint.

Voltage

- 120V, 208V, 240/208V, 1-phase.

Construction

- 22-gauge steel cabinet, 20-gauge steel grille.
- High-limit temperature control with manual reset.
- Additional one-time thermal fuse.

Fan

- Quiet fan.

Heating element

- Nichrome heating element provides instant heat.

Control

- Built-in double-pole thermostat (-T2 models).
- Built-in double-pole thermostat and timer (-T2M models).
- Built-in thermostat kit available.
- Wall thermostat (not included, the use of an electronic thermostat is strongly recommended).

Note: If an electronic wall-mounted thermostat is used, it must be compatible with forced-air heaters.

- Controls located at the top of the unit.

Installation

- 6 in. (150 mm) minimum clearance to floor or any adjacent surfaces.
- May be recessed or surface-mounted with optional surface mounting box.
- Quick and easy installation easily retrofits most popular models.
- Wattage can be selected onsite.

Warranty

- 5-year warranty.

Application

- Kitchen, family room, bathroom (model with timer and thermostat), entrance way, office.

Models

Watts ¹	Volts	Product #	Product #	Product #	BTU/hr	Weight	
		Without thermostat ²	Built-in thermostat	Built-in thermostat and timer		lb	kg
1000 or 500	120	OVOU1002BL	OVOU1002BL-T2	OVOU1002BL-T2M	3413 or 1706	7.4	3.4
1500 or 750	120	OVOU1502BL	OVOU1502BL-T2	OVOU1502BL-T2M	5119 or 2560	7.4	3.4
1000 or 500	208	OVOU1008BL	OVOU1008BL-T2	OVOU1008BL-T2M	3413 or 1706	7.4	3.4
2000 or 1000	208	OVOU2008BL	OVOU2008BL-T2	OVOU2008BL-T2M	6825 or 3413	7.4	3.4
1000/750 or 500/375	240/208	OVOU1000BL	OVOU1000BL-T2	OVOU1000BL-T2M	3413/2560 or 1706/1280	7.4	3.4
1500/1125 or 750/560	240/208	OVOU1500BL	OVOU1500BL-T2	OVOU1500BL-T2M	5119/3839 or 2560/1911	7.4	3.4
2000/1500 or 1000/750	240/208	OVOU2000BL	OVOU2000BL-T2	OVOU2000BL-T2M	6825/5119 or 3413/2560	7.4	3.4

Options

Product # Kit	Description
KIT-OVO-BB6	Back box (6 pack)
KIT-OVO-BSBL	Surface mounting box
KIT-OVO-T1BL	Single-pole thermostat, 120V-600V
KIT-OVO-T2BL	Double-pole thermostat, 120V-277V

Standard color is white.

Add -SBE after BL for unit without back box. (Available for United States market only.)

¹ Wattage can be selected onsite.

² Requires non pulsing wall-mounted thermostat. Please refer to the Wall Thermostats Reference Chart at the end of the catalog.

