

XCE Xlerator High Velocity Hand Dryer



Features

Color

- Standard: white (W).

Finish

- Standard: epoxy/polyester powder paint.
- Optional : White polymer BMC (BW), P126 (C), graphite (GR) or brushed stainless steel (SB).

Voltage

- 110-120V, 208-240V, 1-phase

Construction

- Standard die cast zinc alloy monobloc housing.

Fan

- Motor operating at 20,000 rpm.
- Air volume at high velocity of 19,000 lfm.
- Adjustable motor speed.
- Includes 1.1 in. noise reduction nozzle which brings the sound level down to 71 dBA (81 dBA with hands).

Heating element

- Helical coil nickel-chromium alloy wire mounted inside the blower housing.
- Adjustable heat control : High, Medium, Low and Off.

Control

- Infrared optical sensor to activate hand dryer.
- 35 second lockout feature if hands are not removed.

Installation

- Surface mounted.

Warranty

- 5-year warranty against defects.

Application

- Bar, school, penitentiary, restaurant, commercial mall.

Models

Product #	Price	Color ¹	Volts	Watts	No heat watts	Weight	
						lb	kg
XL-W-11N-110-120V	1508.00	W	110-120	1240-1450	460-530	17	7.7
XL-BW-11N-110-120V	1396.00	BW				15	6.8
XL-GR-11N-110-120V	1589.00	GR				17	7.7
XL-C-11N-110-120V	1939.00	C				17	7.7
XL-SB-11N-110-120V	2065.00	SB				16	7.3
XL-W-11N-208-240V	1508.00	W	208-240	1160-1490	425-500	17	7.7
XL-BW-11N-208-240V	1396.00	BW				15	6.8
XL-GR-11N-208-240V	1620.00	GR				17	7.7
XL-C-11N-208-240V	1939.00	C				17	7.7
XL-SB-11N-208-240V	2065.00	SB				16	7.3

¹ W (White), BW (White polymer BMC), GR (Graphite), C (Chrome), SB (Brushed stainless steel). Eco model available on demand (-ECO).

Options

# Produit Kit	Price	Description
XL-40502	840.00	ADA compliant stainless steel recess
XL-C-89S	210.00	Wall guard – stainless steel
XLP-89B	282.00	Microban® anti-microbial plastic wall guard - black
XLP-89W	282.00	Microban® anti-microbial plastic wall guard - white