

OVR Register Wall Fan Heater



With Surface Mounting Box and Thermostat

Recessed with Thermostat



Features

Color

- Standard: white, almond.
- Optional (upcharge applicable): metallic silver, bronze, metallic charcoal, aluminum, semi-gloss black, sand.
- Custom colors available upon request.

Finish

- Standard: epoxy/polyester powder paint.

Voltage

- 120V, 208V, 240/208V, 1-phase.

Construction

- 20-gauge steel.
- High-limit temperature control with automatic reset.

Fan

- Quiet fan operating.
- 500W to 1000W; 40 cfm fan and 1250W to 2000W; 80 cfm fan.
- Factory-lubricated motor.

Heating element

- Durable tubular heating element with fins.
- Factory sealed element upon request.

Control

- Built-in thermostat available with a control knob or tamperproof.

Note: If an electronic thermostat is used, it must be compatible with forced-air heaters.

Installation

- The air outlet should be installed at least 10 in. (25.4 cm) above floor.
- Quick installation with recess box mounting holes.
- Large wiring compartment.
- May be recessed in 2 in. x 3 in. stud partitions.
- Surface mounting box available.
- Tight fit with V-shaped recess box.

Warranty

- 5-year warranty against defects.

Application

- Entrance way, kitchen, bathroom, family room, basement.

OVR

Models

Product #	Product # with Built-In Thermostat	Volts	Watts	Weight	
				lb	kg
OVRU0502	OVRU0502BL-TB6	120	500	9.0	4.1
OVRU0752	OVRU0752BL-TB6	120	750	9.0	4.1
OVRU1002	OVRU1002BL-TB6	120	1000	9.0	4.1
OVRU1252	OVRU1252BL-TB6	120	1250	9.0	4.1
OVRU1502	OVRU1502BL-TB6	120	1500	9.0	4.1
OVRU0500	OVRU0500BL-TB26	240/208	500/375	9.0	4.1
OVRU0750	OVRU0750BL-TB26	240/208	750/563	9.0	4.1
OVRU1000	OVRU1000BL-TB26	240/208	1000/750	9.0	4.1
OVRU1250	OVRU1250BL-TB26	240/208	1250/938	9.0	4.1
OVRU1500	OVRU1500BL-TB26	240/208	1500/1125	9.0	4.1
OVRU2000	OVRU2000BL-TB26	240/208	2000/1500	9.0	4.1
OVRU2008	OVRU2008BL-TB26	208	2000	9.0	4.1

Options

Product # Kit	Product # Factory installed*	Description
KIT-OVR-BS	-	Surface mounting box
KIT-OVR-DIS ³	DIS ³	Disconnect switch, 20A at 277V max.
-	ES ¹	With sealed element factory installed
KIT-OVR-TB6	TB6	Single-pole bi-metal thermostat
KIT-OVR-TB26 ²	TB26 ²	Double-pole bi-metal thermostat
KIT-OVR-TB6-AV	TB6AV	Single-pole bi-metal thermostat, tamperproof
KIT-OVR-TB26-AV ²	TB26AV ²	Double-pole bi-metal thermostat, tamperproof

* For factory installed options, add the option number to the product number. See the Product Code section inside the front cover.

¹ The option "sealed element" increases the reliability of these in humid environments. It does not completely eliminate the leakage currents of metal sheathed heating elements.

² "Off" position.

³ For the U.S. only; The nominal current of the unit must not exceed 80% of the capacity of the disconnect.

Add "BL" for white, "AM" for almond.

Upcharge available for optional colors shown in the color chart section.

